FALL PROTECTION

FIXED BEAM ANCHORS

• Installs in seconds to the beam structure in any orientation

Final tightening using a built-in adjustment handle Fits up to 1 1/2" thick beam flange, 2 1/2" to 12" wide

Model No. SEE808 Mfg. No. 2108406 Price/Each \$







FREESTANDING COUNTERWEIGHT ANCHORS

Freestanding system is easily placed on top of the roof surface to provide tie-off point for one worker

Model No. SEE809 Mfg. No. 7200439 Price/Each \$







LAD-SAF™ ROPE GRABS

- Mobile design automatically follows users for hands-free operation
- Detachable design can be attached or removed anywhere along lifeline
- Inertia and cam locking systems for safety and to prevent "panic-grab"
- For use on 5/8" (16 mm) polyester/polypropylene rope lifeline

• Use with 3' shock absorbing lanyard

Model No. SEB433 Mfg. No. 5000335C Price/Each \$







- 30' lifeline
- 5/8" diameter
- Snap hook at one end
- Features additional abrasion and UV resistance, for added durability, longevity, and safety

Model No. SEC130 Mfg. No. 1202754C Price/Each \$





COBRA™ ROPE GRAB

- Constructed of high impact resistant steel
- Operates in automatic or manual mode
- Can be used on approved horizontal rope systems
- Can be removed and reattached to rope at any point during traverse
- Designed for use with nylon or polyester rope
- Accommodates 5/8" (16 mm) rope
- Total weight: 1.75 lbs. (0.79 kg)
- Certified to CSA standard Z259.2.1

Model No. SEB385 Mfg. No. AC202C Price/Each \$









GLYDER™ II SLIDING BEAM ANCHORS

- Wear pads eliminate metal-to-metal contact, for smooth operation
- Easy installation
- Dual beam grip adjustment prevents twisting and turning
- Extremely light weight at only 3.7 lbs.
- User capacity of 420 lbs.
- Fits flange 3 1/2" to 14" wide and up to 1 1/4" thick

Model No. SEB435 Mfg. No. 2104700 Price/Each \$







DOOR/WINDOW JAMB ANCHORS

- Fits door or window sizes ranging from 21 1/2" to 51 1/2" in width
- Non-penetrating design ensures no damage to structure
- Fast and easy installation with built-in adjustment
- knob no tools or drilling are required Lightweight and extremely portable design

Model No. SEJ618 Mfg. No. 2100080 Price/Fach \$









BEAM TROLLEY ANCHORAGE CONNECTORS

- · Installs easily and quickly overhead with no tools necessary at ends or midpoint on beams
- Non-corrosive double-shielded wheel bearings provide smooth and effortless operation
- Trolley guards protect the wheels from damage and keep the beam ahead of the trolley clear of debris
- Provides added maneuverability, improved safety, and increased productivity
- Fits flat or tapered beam flanges 3" to 8" wide, and up to 11/16" thick

Model No. SEJ617 Mfg. No. 2103143 Price/Each \$







ROPE LIFELINES

- 16 mm (5/8") diameter, polyester sheath with polypropylene core
- Tensile strength: 2540 kg (5600 lbs.)
- · Zinc plated stamped steel hook
- Net weight: 5.6 lbs. (25 kg)







Model No.	Mfg.	Length'	Price /Each
	No.		
SEB381	SSR100-50	50	
SEB382	SSR100-100	100	