ZX-1 PREMIUM NITRILE FOAM PALM COATED GLOVES

- Sanitized® coating inhibits bacteria, minimizes odour development, and promotes freshness
- Black foam nitrile palm coating for optimal grip in dry, wet and oily conditions
- Grey seamless nylon/spandex 15-gauge shell for optimal dexterity
- Foam nitrile coating improves abrasion resistance
- Premium comfort and breathability reduces hand fatigue
- Knit wrist prevents dirt and debris from entering the glove
- EN 388 Performance Levels: 4131
- EN 420 Dexterity Level: 5

Applications: Automotive, small parts handling, quality inspection, assembly and maintenance, manufacturing

ZENITH® Safety Products

SDP441

Priced per Pair

Model No.	Size	Price /Each
SDP438	6	
SDP439	7	
SDP440	8	
SDP441	9	
SDP442	10	
SDP443	11	

ZX-2 PREMIUM 3/4 NITRILE & NITRILE FOAM PALM COATED GLOVES

- Sanitized® coating inhibits bacteria, minimizes odour development, and promotes freshness
- Black foam nitrile palm coating for maximum grip in dry, wet and oily conditions
- Purple flat nitrile 3/4 coating to prevent liquids from permeating through the glove shell
- Grey seamless nylon/spandex 18-gauge shell for maximum dexterity
- Premium comfort and breathability reduces hand fatigue
- Knit wrist prevents dirt and debris from entering the glove
- EN 388 Performance Levels: 4121

Applications: Automotive, small parts handling, assembly and maintenance, manufacturing, wet/oily applications

ZENITH® Safety Products

SDP446

Priced per Pair

Model No.	Size	Price /Each
SDP444	7	
SDP445	8	
SDP446	9	
SDP447	10	
SDP448	11	

ZX-30° PREMIUM FOAM PVC PALM COATED ACRYLIC LINED GLOVES

- Sanitized® coating inhibits bacteria, minimizes odour development, and promotes freshness
- Foam PVC palm coating offers excellent breathability, dexterity and durability, while providing a superior wet or dry grip
- 15-gauge seamless nylon/spandex shell with 100% acrylic lining for superior cold protection
- Uncoated back permits breathability and limits perspiration
- Exceptional comfort and fit
- Resists abrasions, cuts and punctures
- Meets EN 511 standards for extreme cold protection maintaining flexibility in temperatures up to -50°C
- EN 511 Contact Cold Resistance Level: 2
- EN 388 Performance Levels: 3232

Applications: Cold/outdoor environments, fishing industry, glass/wood handling, construction, general maintenance

ZENITH® Safety Products

SFQ726

Priced per Pair

Model No.	Size	Price /Each
SFQ726	Medium (7)	
SFQ727	Large (8)	
SFQ728	X-Large (9)	
SFQ729	2X-Large (10)	