## **CHEMICALS**

#### PREMIUM 100% RTV SILICONE SEALANT

- Excellent adhesion to non-porous materials
- Provides a watertight seal
- Highly, permanently flexible
- Will not crack, crumble or shrink
- Resists moisture and mildew
- Interior/exterior use
- Size: 10 oz



### SUPERFLEX<sup>TM</sup> BLUE RTV SILICONE ADHESIVE **SEALANT**

- · Cures to a tough, flexible rubber
- "Formed in Place" gaskets resist shrinking, cracking and migrating
- Fills gaps to 0.25"
- Coats pre-cut gaskets
- Low volatility
- Tack free in 30 min 24 hrs., full strength
- Temperature range -65°F to 500°F (-54°C to 260°C) intermittent
- Colour: Blue



#### Will not slump in overhead or vertical applications Withstands extreme temperature cycling, U.V. light and ozone Cannot be painted Tack free in 30 min. 24 hrs., full strength Temperature range -65°F to 450°F (-54°C to 232°C) intermittent Accepted for use in Canadian food processing facilities LOCTITE.

## WHITE LIGHTNING

	Price
Colour	/Each
Clear	
White	
Aluminum	
Black	
	Clear White Aluminum

### LOCTITE.

Model No.	Mfg. No.	Size	Price /Each
AC198	30560	80 ml tube	
AC199	30533	300 ml cartridge	

Model No.	Mfg. No.	Size	Colour	Price /Each
AC157	59330	80 ml tube	Black	
AC158	59375	300 ml cartr.	Black	
AC196	59530	80 ml tube	Clear	
AC197	59575	300 ml cartr.	Clear	
AC121	59430	80 ml tube	White	
AC113	59475	300 ml cartr.	White	

SUPERFLEX<sup>TM</sup> SILICONE

**ADHESIVE SEALANT** 

adhesive, cures at room temperature

General purpose, one part silicone

to form a tough rubber seal

#### 3006™ ALL PURPOSE **ADHESIVE CAULK**

- High quality acrylic latex formulation with silicone additives
- Cured caulk resists rust and mildew Applies a smooth, professional bead
- without gaps or bubbles Maintains excellent
- flexibility and elasticity
- Excellent colour retention
- Can be painted or stained after curing
- Interior/exterior use
- Exceeds ASTM Spec. C-834
- Size: 10 oz.



#### SUPERFLEX™ RED HIGH TEMP RTV SILICONE

- Resists aging, weather and thermal cycling without shrinking, cracking or hardening
- Fills gaps to .25"
- Tack free in 30 min. 24 hrs., full strength
- Resist temperatures to 600°F (315°C) intermittent
- Colour: Red

LOCTITE

Accepted for use in Canadian food processing facilities

> Mfg. No.

59630

59675



Size

80 ml tube

300 ml cartridge

#### 598™ BLACK RTV SILICONE **GASKET MAKER** Adheres well to oily surfaces

- Low odour and volatility
- Fills gaps to 0.25"
- Forms tough, flexible gaskets directly on the flange
- Resistant to most chemicals and solvents
- Non-corrosive
- Tack free in 30 min. 24 hrs., full strength
- Temperature range: -75°F to 625°F (-59°C to 329°C) intermittent
- Colour: Black
- Accepted for use in Canadian food processing facilities



## LOCTITE

Model No.	Mfg. No.	Size	Price /Each
AA488	59830	70 ml tube	
AC195	59875	300 ml cartridge	



Model No.	Colour	Price /Each
AD884	White	

#### Model AC166


#### **CONTRACTOR RTV** SILICONE SEALANT

- Made with 100% silicone
- Flexible watertight seal Minimal shrinking
- Interior/exterior use
- Size: 10 oz





# WHITE LIGHTNING



#### PAINTER'S PREFERRED™ CAULK

- High quality acrylic latex formulation
- Cured caulk resists rust and mildew
- Applies a smooth, professional bead without gaps or air bubbles
- Can be painted when thoroughly dry
- Meets performance requirements of ASTM C-834 for extension recovery and adhesion
- · Colour: White





Model No.	Size	Price /Each
AD882	10 oz.	



