GORILLA CONSTRUCTION ADHESIVE

- Tough, versatile and all-weather adhesive
- 100% adhesive formula creates heavy-duty bonds
- 100% waterproof
- Holds in 30 seconds
- Low-odor
- Gap filling up to 1"
- Can be painted with latex paint within 2 days of application
- Container Type: Cartridge
- · Colour: White
- · Application Time: 10 min.
- For use on: Wood, Metal, Stone, Ceramic, Glass, Most Plastics, PVC Sheet, Brick, Paper, Rubber



| Model | | Price |
|-------|------|-------|
| No. | Size | /Each |
| AE412 | 0.07 | |

NUFLEX®458 SUB-FLOOR CONSTRUCTION ADHESIVE

- Ideal for particleboard, OSB and engineered lumber as well as wet, frozen and treated lumber
- Provides superior adhesive strength and remains permanently flexible
- Fills gaps and irregularities between materials and provides a more solid backup surface
- Reduces the amount of nailing, increases floor rigidity and helps eliminate squeaky floors
- · Exceeds AFG-01 specifications
- Freeze-thaw stable
- Superior extreme temperature adhesive; works extremely well in colder temperatures and offers excellent water-resistance






| Model No. | Mfg. | | Price /Each |
|--------------|-------|--------|----------------|
| | No. | Size | |
| AE622 | 45880 | 828 ml | |


CARPENTER'S® WOOD GLUE

- Made for furniture repair and general indoor household projects
- Best for soft and hardwoods, particle board and porous materials
- Cleans up with soap and water when wet, and scrape and sand when glue is dry
- Open time: 10-15 minutes before clamping
- · Clamp time: 12 hours
- Light colour for natural and light stained woods
- Pourable
- Colour when dry: Yellow





TEN BOND CONTACT CEMENT



 Air drying adhesive which bonds immediately and permanently upon application of contact pressure

 No clamping or fixturing required



| Model No. | Mfg. No. | Size | Price /Each |
|--------------|-------------|--------|----------------|
| AMC295 | 10-1L | 1L | |
| AMC294 | 10-1GAL | 1 gal. | |

NUFLEX®480 POLYURETHANE CONSTRUCTION ADHESIVE

- Excellent adhesion strength
- · 100% polyurethane based, VOC compliant adhesive
- Can be used for interior or exterior projects and is three times as strong as conventional solvent based construction adhesives
- Ideal for wood, hardwood flooring, concrete, stone, marble, slate, masonry, brick, foam insulation, carpets, metal, lead, cement-based products, ceramics, fiberglass, drywall and mirrors
- · Contributes to LEED credit
- · Low-odor
- · Adheres to dry, wet and frozen lumber
- Waterproof, paintable and cures even in cold temperatures
- AFG-01 approved



| Model No. | Mfg. No. | Size | Price /Each |
|--------------|-------------|--------|----------------|
| AE623 | 48000 | 296 ml | |
| AE624 | 48080 | 828 ml | |

PROBOND® MAX WOOD GLUE

- Made for furniture repair and general indoor and outdoor household projects
- Best on wood
- Contains real wood fibers for superior staining, painting, and sanding
- Open time: 10-15 minutes before clamping
- · Clamp time: 12 hours
- Easy to clean-up with water
- Pourable and waterproof
- · Colour when dry: Beige





| Model | Mfg. | | Price |
|-------|-------|--------|-------|
| No. | No. | Size | /Each |
| AE615 | 69220 | 118 mL | |
| AE616 | 69221 | 236 mL | |
| AE617 | 69222 | 473 mL | |
| AE618 | 69224 | 3.8 L | |

ORIGINAL GORILLA GLUE

- · Incredibly strong and versatile glue
- Water-activated
- 100% waterproof
- Expands by about 3-4 times the applied amount
- · Unaffected by extreme heat or cold
- For use indoors and outdoors
- · Colour: Tan
- Application Time: 10 min.
- Full Cure Time: 24 hrs.
- Open Working Time: 10-15 minutes
- Clamp time: 1-2 hours
- · Drying Time: 24 hours
- For use on: Wood, Metal, Stone, Ceramic, Glass, Most Plastics, PVC Sheet, Brick, Paper



| Model No. | Format | Container Type | Price /Each |
|--------------|---------|-------------------|----------------|
| NKA481 | 4 x 3 q | Tube | |
| NKA497 | 2 oz. | Squeeze Bottle | |
| NKA480 | 4 oz. | Squeeze Bottle | |
| NKA498 | 8 oz. | Squeeze Bottle | |

WHITE GLUE

- · Washable no-run glue; easy to clean up
- Safe and non-toxic
- Pourable
- Recommended for wood, wood compositions, veneer, paper, cardboard, leather, fabric and cork
- Not recommended for joints that require gap filling, bonding non-porous substrates (i.e. plastic or metal)
- Colour: White





| Model | Mfg. | | Price |
|-------|------------|--------|-------|
| No. | No. | Size | /Each |
| AE606 | 60307W8 | 120 ml | |
| AE607 | 60310Q | 225 ml | |
| AE608 | 6155060331 | 950 ml | |
| AE609 | 6155060341 | 3.8 L | |

ULTIMATE® POLYURETHANE GLUE

- The ultimate adhesive; adheres to anything with a permanent, strong, waterproof bond
- Indoor and outdoor
- · Does not require any mixing
- · Sandable and paintable
- Best on stone, metal, ceramic, wood, foam, glass, etc.
- Open time: 30 minutes before clamping
- Clamp time: 12 hours
- Clean up: mineral spirits or acetone when glue is wet; sanding and scraping when glue is dry
- Colour when dry: Yellow





| Model | Mfg. | | Price /Each |
|-------|------------|--------|----------------|
| No. | No. | Size | |
| AE619 | 6155069406 | 60 mL | |
| AE620 | 69416 | 236 mL | |