

DYNASTRAIGHT® AIR POWERED ABRASIVE FINISHING TOOLS

- Ideal set-up for Dynacushion® wheel (not included)
- Threaded arbor (5/8" -11) for exclusive use with Dynacushion® pneumatic wheel
- Shown with optional pneumatic wheel

Model No. TGY774
Mfg. No. 13505
Abrasive Information: 15-1/2" long x 3-1/2" wide Dynacushion® belts (394 mm x 89 mm)
Air Flow Rate @ 90 PSI: 44 SCFM
Sound Level: 88 dB (A)
Horsepower: 1.00 HP
Free Speed: 3400 RPM
Air Pressure: 90 PSI
Air Inlet Thread: 3/8 NPT
Hose Size (I.D.): 3/8" (10 mm)
Threaded Arbor: 5/8" - 11 male
Tool Spindle Thread: 1/2" - 20 male
Length: 14 7/8" (378 mm)
Height: 1 7/8" (48 mm)
Weight: 4 lbs. (1.82 kg)
Price/Each: \$



DYNISHER® FINISHING TOOLS

- Excellent for blending and finishing stainless steel and most other metals, leaving an in-line pattern
- Includes: 3/4" dia. arbor for mounting a variety of abrasives & accessories
- Shown with optional Dynacushion® pneumatic wheel not included

Model No TGY767
Mfg. No. 13450
Abrasive Information: 3-1/2"(84 mm) x 15-1/2"(394 mm) abrasive belts 4" dia. (102 mm) Abrasive flap wheels 4" (102 mm) dia. conditioning discs 42 SCFM
Air Flow Rate @ 90 PSI: 42 SCFM
Sound Level: 80 dB (A)
Horsepower: 1.00 HP
Free Speed: 2800 RPM
Air Pressure: 90 PSI
Air Inlet Thread: 3/8 NPT
Hose Size (I.D.): 3/8" (10 mm)
Max. SFPM: 3665 SFPM
Arbor Information: 3/4" x 2 5/16" (19 mm x 59.5 mm)
Length: 15" (381 mm)
Height: 7" (178 mm)
Weight: 5.7 lbs. (2.59 kg)
Price/Each: \$



DIE GRINDERS STRAIGHT & OFFSET (7°)

- Gearless motor reduces downtime and lessens repair expense compared to geared tools
- Governor-controlled to maintain RPM under heavy load
- Lightweight thermal-insulated housing reduces cold air transmission and vibration to the operator



4" LIGHTWEIGHT DYNINGER® FINISHING TOOLS (1/4" COLLET)

- Mount 4" dia. spindle-mount dry-cut sanding stars with 1/4" shank. Order stars separately
- Tool includes air-flow control Dynaswivel® fitting for maximum tool manoeuvrability and control
- Eliminates raised grain and removes loose fibres when whitewood sanding as well as scuffing sealer coats

Model No TGY792
Mfg. No. 52050
Abrasive Information: -
Order Separately: 3/4", 1", 1-1/2", 2", 3", & 4", dia. sanding stars (19, 25, 38, 51, 76, & 102 mm)
Air Flow Rate @ 90 PSI: 21 SCFM
Sound Level: 81 dB (A)
Horsepower: 0.40 HP
Free Speed: 0 to 3200 RPM
Air Pressure: 90 PSI
Air Inlet Thread: 1/4 NPT
Hose Size (I.D.): 1/4" (6 mm)
Max. SFPM: 3350 SFPM
Tool Spindle Thread: 3/8"-24 male
Length: 8 3/4" (222 mm)
Height Diameter: 2 3/8" (60 mm)
Weight: 2.2 lbs. (1 kg)
Price/Each: \$



Model No.	TGZ172	TGZ174	TGZ175	TGZ073
Mfg. No.	52666	52668	52669	48205
Head type	Straight	Straight	Straight	7°
Collet Insert Size:	1/4"	1/4"	1/4"	1/4"
Free Speed (RPM):	12 000	18 000	20 000	25 000
HP (W):	1.0 (746)	1.0 (746)	1.0 (746)	0.4 (224)
Motor Characteristic:	Gearless	Gearless	Gearless	Gearless
Exhaust Type:	Rear	Rear	Rear	Rear
Wt. lbs.:	2.3	2.4	2.4	1.5
Price/Each:				

PENCIL GRINDERS 60 000 RPM

- High-speed air motor, controlled with patented governor, provides constant speed under load
- Precision, high-tolerance, low run-out collet. Run-out is a true 0.0002 @ 1" (25 mm) from face
- Super flexible hose for maximum agility

Model No. TGZ034
Mfg. No. 51700
Collet Insert Size: 1/8"
Air Flow Rate @ 90 PSI: 8 SCFM
Sound Level: 66 dB(A)
Motor Characteristic: Oil-Less Turbine
Free Speed: 60 000 RPM
Bearing Type: Metal
Exhaust Type: Rear
Weight: 0.6 lbs.
Packaged Weight: 1.6 lbs.
Price/Each: \$



ELECTRIC DYNISHER® FINISHING TOOLS

- 3/4" (19 mm) dia. arbor; pneumatic tire and abrasive sold separately
- Variable speed On/Off switch
- 5/8" - 11 spindle and 3/4" arbor

Model No THZ358
Mfg. No. 51585
Max. RPM: 0-3000 RPM
Voltage: 120 V (AC) Phase: 1
Current: 11 A, 60 Hz Frequency
Length: 17" (468 mm)
Height: 8" (468 mm)
Weight: 9.5 lbs. (3.8 kg)
Price/Each: \$

