

# EMERGENCY LIGHTS

## STELLA EXIT SIGNS

- C860 approved
- Standard 120/347VAC input (hardwire) and sealed nickel-cadmium batteries provide a minimum of 30 minutes of emergency duration
- Uses 2 W LED board
- Long life LED light source
- Knockout chevrons
- 20-gauge steel construction with baked powder coat white paint finish
- Pre-stamped universal mounting and keyhole slots on backplate



XB930



XB933



Model No.	Mfg. No.	Description	Dimensions				Price /Each
			W"	x	D"	x	H"
XB930	SLE-SP-L-R-U-M	Exit	12	x	2.25	x	7.5
XB933	SLS-L-R-U-M-UDC	Sortie	18.5	x	2.25	x	7.5

## STELLA COMBINATION SIGNS

- C860 approved
- LED EXIT and SORTIE models 120/277/347 VAC dual input (hard wire)
- Push button test switch
- Self-powered for minimum 30 minutes -6 VDC 36 W
- Solid state transfer charger
- Dual diagnostic LEDs indicate AC-ON and CHARGE
- Brownout and low voltage protection
- Two top mounted high impact thermoplastic PAR18 9 W tungsten heads
- Knockout chevrons
- 20-gauge steel construction with baked powder coat white paint finish



Model No.	Mfg. No.	Description	Price /Each
XB929	SLE-6-36-L-R-U-M-2SR/9W	Exit	
XB932	SLS-6-36-L-R-U-M-2SR/9W	Sortie	

### REPLACEMENT BULB

XB338	LP104	9 W Tungsten
-------	-------	--------------

## STELLA RUNNING MAN EXIT SIGNS

- Feature 120/347 VAC dual input (hardwire), universal DC; 6-24 VDC or self-powered
- Running Man sign uses a 2 watt LED source
- Long life LED light source
- Universal pictograms included showing left indicators, right indicators and no indicators
- 20-gauge steel construction with white baked powder coat paint finish
- Pre-stamped universal mounting and keyhole slots on backplate

**Model No. XE661**  
**Mfg. No. SL-RM-L-U-0LR-M (AC)**  
**Price/Each \$**

**Model No. XE662**  
**Mfg. No. SL-RM-SP-L-U-0LR-M (Self-powered)**  
**Price/Each \$**

**Model No. XE663**  
**Mfg. No. SL-RM-L-U-0LR-M-UDC (6-24 VDC)**  
**Price/Each \$**



XE661



## STELLA RUNNING MAN COMBO EXIT SIGNS

- Running Man models are supplied with 120/347 VAC dual input (hardwire)
- Push button test switch
- Self-powered for minimum 30 minutes - 6V DC 36W
- Solid state transfer charger
- Dual diagnostic LEDs indicate AC-ON and CHARGE
- Brownout and low voltage protection
- Two top mounted high impact thermoplastic PAR18 9-watt tungsten heads
- Universal pictograms included showing left indicators, right indicators and no indicators
- 20-gauge steel construction with white baked powder coat paint finish
- Certified for sale in Canada by an accredited certification body

**Model No. XE664**  
**Mfg. No. SL-RM-6-36-L-U-0LR-M-2SR/9W**  
**Price/Each \$**



## TEMPESTA™ LED EMERGENCY LUMINAIRES

- Uses two LED modules that are wired in parallel
- Will only illuminate during a power failure
- LEDs are rated for 100 000 hours at L70
- Input Voltage: 120 - 347 V
- Wattage: 17 W
- High quality corrosion, flame and vandal resistant polycarbonate housing
- Comes standard with a Ni-MH battery pack that provides a minimum of 30 minutes of emergency lighting
- IP65 Rating



Model No.	Mfg. No.	Description	Dimensions				Price /Each
			L"	x	W"	x	H"
XE874	TA-LED-EM-120-347V-S	Surface Mounted	17	x	6 1/2	x	3 1/2
XE875	TA-LED-EM-120-347V-R	Recessed	19 1/4	x	9 1/2	x	3 1/2
XE876	TA-LED-EM-120-347V-TB	T-Bar Mount	23 3/4	x	7 1/2	x	4

## ILLUMINA® BS100 SERIES IP66 VAPOR-TIGHT

- Lightweight, durable 100% corrosion, flame and vandal resistant polycarbonate construction
- Designed to be resilient, highly efficient and easy to install
- For ceiling, wall, suspension and pendant installations
- UV stabilized to reduce the yellowing index
- Liquid silicone memory retention gasket allows for installations in wet locations
- Incorporates a "dual concave" parabolic high-output, metallized reflector
- Also approved for through wiring application



Model No.	Mfg. No.	Volts	Price /Each
XC441	BS10048T8232AC120V	120	
XC442	BS10048T8232AC347V	347	