INSPECTION CAMERAS

SEESNAKE® MICROTM **INSPECTION CAMERAS**

The CA-100 inspection camera allows you to perform more detailed visual inspections in even harder-to-reach areas. The micro[™] CA-100 comes standard with a rugged 3/4" (17 mm) anodized aluminum camera head with four super bright LEDs. Easily rotate the active image counter-clockwise to see in any situation.

SPECIFICATIONS:

Display:	3.5" colour LCD (320 x 240 resolution)
Camera head:	Aluminum 17 mm
Lighting:	4 adjustable LEDs
Cable reach:	3' (Expandable to 30'
	w/ optional extensions)
Video output:	3' RCA cable (included)
Waterproof:	Camera head and cable to 10'
	(when properly assembled)
Power source:	4 AA batteries
Attachments:	Mirror, hook and magnet



RIDGID

Model	Mfg.		Price	
No.	No.	Description	/Each	
IA840	36738	micro™ CA-100 Inspection Camera		
IA841	37103	17 mm Replacement Imager		
IA842	37108	3' Cable Universal Extension		
IA843	37113	6' Cable Universal Extension		

RECORDABLE BORESCOPE INSPECTION CAMERA

- Camera and video functions save high resolution images and video
- Comfortable pistol grip design
- High-resolution, 2.5", color, LCD monitor
- Waterproof (IP67) camera head
- 39" (m) gooseneck cable retains configured shape
- Expandable cable up to 30 ft. (9m) with extensions (optional) •
- . Four high-visibility LED lights
- 180° mirror rotation function
- Low battery indicator and auto shut off after 10 minutes
- Expandable memory up to 32Gb (SD card sold separately)
- Includes: Video Borescope Inspection Camera, Recordable, 9mm Camera Head, Camera Probe, Borescope, Magnet, Hook and Mirror Attachments, Batteries, USB Cable, and Hard Carrying Case Display Size: 2.5"
- Resolution: 640 x 480 pixels
- Camera Head: 9 mm (0.35")
- Frames Per Second (FPS): 30
- Playback: Photo (JPEG) and Video (AVI)
- Digital Zoom: 4x
- Time and Date Stamp: Yes
- Data Output: USB/SD Card
- Power Supply: 4 AA Batteries
- Operating Temperature:
- 14 to 122°F (-10 to 50°C)



Model No.	Mfg. No.	Description	Pri /Ea
IB888	R8500	Recordable Borescope Inspection Camera	
IB889	R8500-3MEXT	9.84' (3 m) Cable Extension	
IB894	R8500-3.9MM	3.9 mm Camera Head	
IB892	R8500-ART	5.5 mm Articulating Camera	
IB893	R8500-RCH	Replacement 9 mm Camera Head on 39" (1 m) Cable	
IB890	R8500-5M9MM	Replacement 9 mm Camera Head on 16.4' (5 m) Cable	
IB891	R8500-20M	Replacement 9.8 mm Camera Head on 65.6' (20 m) Cable	

MICRO[™] CA-350 INSPECTION CAMERAS

Documentation made easy with the new Ridgid® micro[™] CA-300 inspection camera. Easily record still images and videos of problems. Comfortable pistolgrip design, large screen, and rugged anodized aluminum camera head with four bright LEDs. Features image rotation and digital zoom.

SPECIFICATIONS:

Display: Camera diameter: Lighting: Cable reach: Images: Video: **External memory:** Power source: Included:

3.5" (90 mm) colour TFT 0.66" (17 mm) LCD (320 x 240 resolution) 4 adjustable LEDs

3' (0.9 m) (Expandable to 30' with optional extension also compatible with microDrain[™], microReel[™] and nanoReel[™]) JPG - Good (640 x 480), Better (1024 x 768), Best (1600 x 1200) AVI - Good (320 x 240), Best (640 x 480) SD card up to 32 GB (4 GB SD card included)

Rechargeable 3.7 V Li-Ion battery micro[™] CA-300 with 17 mm imager, battery, charger, USB card, hook, magnet and mirror accessories, RCA cable, AC adapter, headset with microphone, 4 GB SD card, 1-year RidgidConnect[™] basic subscription



SILXGI

Model No.	Mfg. No.	Description	Price /Each
IA844	55898	micro™ CA-350 Inspection Camera	
IA841	37103	17 mm Replacement Imager	
IA842	37108	3' Cable Universal Extension	
IA843	37113	6' Cable Universal Extension	
IA845	37083	3.7 V Li-Ion Battery	
IA846	37098	3' (6 m) Imager Head	

R9000 PIPE VIDEO INSPECTION SYSTEM

- Cost effective portable inspection camera
- Designed to deliver quality video inspection in a wide range of applications including: sewers, building ducts/piping, wells, and power plants
- System includes camera head, cable reel, battery pack and DVR
- · Camera head contains 12 white LED lights, a flexible spring coiled joint to navigate corners, a scratch-resistant
- sapphire lens cover and a stainless steel housing that
- allows the camera to withstand various hits • High resolution CCD chip is designed to capture bright,
- crisp, colour video of the inspection area Cable reel is mounted and rotatable
- in the case, therefore the cable can be extended without the need to hold the reel
- Sun visor is included to act as a sun shield for outdoor inspections
- DVR Resolution: 800 x 480 RGB
- DVR Output: TV and Audio
- External Memory: Supports SD memory card up to 32GB
- Viewing Angle: 140°
- Display Size: 7
- Camera Head: 0.9" (23 mm)



Model No.	Mfg. No.	Description	Price /Each
IB751	R9000	Pipe Video Inspection System	
IB895	R9000-40M	131.2' (40 m) Cable Extension	
IB896	R9000-CAMT	Camera Head with Transmitter	
IB897	R9000-RCV	Portable Inspection Camera Receiver	

INSTRUMENTS, **SCALES & ELECTRICAL**

1545

