

## INDUSTRIAL SCREWDRIVERS



### REVERSIBLE, PISTOL GRIP SCREWDRIVERS

- One hand operation reverse valve
- Compact pistol grip
- Roller clutch
- Shut-off clutch



Model No. TG090  
Model No. TG091

### REVERSIBLE IN-LINE SCREWDRIVERS

- Progressive lever start
- Ideal for centering screws during the fastening cycle
- Roller clutch
- Reversible
- Use for disassembly

Model No. TG092



### REVERSIBLE IN-LINE SCREWDRIVERS

- Push-to-start operation
- Quick change reverse operation
- Shut-off clutch
- Ideal for continuous operation
- Positive shut-off at preset torque

Model No. TG093



| Model No. | Mfg No. | Free Speed RPM | Torque Range in.-lbs. (Nm)<br>Soft-pull-up Work |          | CFM | dBA | Vibration m/s <sup>2</sup> | Overall Length in. (mm) | Net Weight lbs. (kg) | Price /Each |
|-----------|---------|----------------|---|----------|-----|-----|----------------------------|-------------------------|----------------------|-------------|
|           |         |                | Min.  | Max.     |     |     |                            |                         |                      |             |
| TG090     | CP2612  | 1470           | 3.5 (0.4)                                       | 39 (4.4) | 14  | 75  | 2.3-3.9                    | 72 (182)                | 1.8 (0.8)            |             |
| TG091     | CP2611  | 1000           | 3.5 (0.4)                                       | 38 (4.3) | 20  | 76  | <2.5                       | 72 (182)                | 1.8 (0.8)            |             |
| TG092     | CP2621  | 1000           | 3.5 (0.4)                                       | 39 (4.4) | 14  | 77  | 9-35                       | 9.6 (224)               | 2.58 (1.2)           |             |
| TG093     | CP2622  | 1700           | 3.5 (0.4)                                       | 38 (4.3) | 14  | 81  | <2.5                       | 8.8 (223)               | 1.39 (.7)            |             |

1/4" (NPTF) air inlet thread; 3/8" min. hose size.

Noise levels are at 1.0 m per Pneurop Standard 8N-1. Vibration levels are per ISO 8662-1.

## 371 PISTOL-GRIP SCREWDRIVER

- Variable speed control
- Option for top or bottom air inlets
- Chuck Size: 1/4"
- Chuck Type: Keyless



| Model No. | Mfg. No. | Air Consumption | Air Inlet         | Sound Level (dBA) | No Load RPM | Price /Each |
|-----------|----------|-----------------|-------------------|-------------------|-------------|-------------|
| TZ935     | 371      | 29              | 1/4 NPT/1/4" NPTF | 78                | 1800        |             |

## 41 SERIES AIR SCREWDRIVER

- Features a Pistol Cushion Clutch that limits torque to minimize the amount of vibration experienced by the operator
- Designed for heavy-duty work
- Torque Range: 0 - 64.6 in.-lbs.
- Weight: 2.4 lbs.
- Length: 7.6" (193mm)
- Spindle Type: 1/4" Hex Quick Change



| Model No. | Mfg. No.   | Air Consumption | Air Inlet | Sound Level (dBA) | No Load RPM | Price /Each |
|-----------|------------|-----------------|-----------|-------------------|-------------|-------------|
| UAE944    | 41PP17TSQ4 | 20 CFM          | 1/4" NPT  | 78                | 1700        |             |

## DIE GRINDERS STRAIGHT & OFFSET (7°)

- Gearless motor reduces downtime and lessens repair expense compared to geared tools
- Governor-controlled to maintain RPM under heavy load
- Lightweight thermal-insulated housing reduces cold air transmission and vibration to the operator



TGZ172



TGZ073

| Model No.             | TGZ172    | TGZ174    | TGZ175    | TGZ073    |
|-----------------------|-----------|-----------|-----------|-----------|
| Mfg. No.              | 52666     | 52668     | 52669     | 48205     |
| Head type             | Straight  | Straight  | Straight  | 7°        |
| Collet Insert Size:   | 1/4"      | 1/4"      | 1/4"      | 1/4"      |
| Free Speed (RPM):     | 12 000    | 18 000    | 20 000    | 25 000    |
| HP (W):               | 1.0 (746) | 1.0 (746) | 1.0 (746) | 0.4 (224) |
| Motor Characteristic: | Gearless  | Gearless  | Gearless  | Gearless  |
| Exhaust Type:         | Rear      | Rear      | Rear      | Rear      |
| Wt. lbs.:             | 2.3       | 2.4       | 2.4       | 1.5       |
| Price/Each:           |           |           |           |           |

## 4" LIGHTWEIGHT DYNINGER® FINISHING TOOLS (1/4" COLLET)



- Mount 4" dia. spindle-mount dry-cut sanding stars with 1/4" shank. Order stars separately
- Tool includes air-flow control Dynaswivel® fitting for maximum tool manoeuvrability and control
- Eliminates raised grain and removes loose fibres when whitewood sanding as well as scuffing sealer coats

|                         |   |
|-------------------------|---|
| Model No                | TGY792  |
| Mfg. No.                | 52050   |
| Abrasive Information:   | -   |
| Order Separately:       | 3/4", 1", 1-1/2", 2", 3", & 4", dia. sanding stars (19, 25, 38, 51, 76, & 102 mm) |
| Air Flow Rate @ 90 PSI: | 21 SCFM   |
| Sound Level:            | 81 dB (A)   |
| Horsepower:             | 0.40 HP   |
| Free Speed:             | 0 to 3200 RPM   |
| Air Pressure:           | 90 PSI  |
| Air Inlet Thread:       | 1/4 NPT   |
| Hose Size (I.D.):       | 1/4" (6 mm)   |
| Max. SFPM:              | 3350 SFPM   |
| Tool Spindle Thread:    | 3/8"-24 male  |
| Length:                 | 8 3/4" (222 mm)   |
| Height Diameter:        | 2 3/8" (60 mm)  |
| Weight:                 | 2.2 lbs. (1 kg)   |
| Price/Each:             | \$  |

